

Occupational Health Dust Risk Assessment

Location	Shepards Drive Processing Plant
Assessment Type	Occupational Health – Dust Exposure
Shift Pattern	8-hour shift
Breaks	2 × 30 minutes (1 hour's total)
Plant Downtime	Approx. 15 minutes per shift
Assessor	Wesley Jameson
Date	20th February 2026



Executive Summary

An occupational health dust assessment has been undertaken at the Shepards Drive Processing Plant to evaluate employee exposure during normal operations. Monitoring data confirms that dust levels across the facility are very low and well controlled, with the highest recorded exposure at 0.082 mg/m³, representing approximately 8% of the applicable workplace exposure limit.

This indicates that overall dust exposure is over 90% below the recognised safety limits, demonstrating strong control of airborne particulates within the working environment.

Dust levels were highest in expected operational areas such as the RDF baler, cardboard line, and pre-pick line, but remained consistently low across all monitored locations. Importantly, monitoring identified:

- No short-term exposure peaks
- Stable operating conditions
- No exceedances of workplace limits

The assessment concludes that occupational exposure to dust presents a low risk to health, with all areas assessed as either low or very low risk, including control room environments where exposure is minimal. A range of effective control measures are currently in place across the site, including:

- Regular cleaning and maintenance of plant
- Provision of dust masks and face fit testing
- Dust awareness training for employees
- Adequate ventilation throughout the facility

Conclusion

- Dust exposure at the Shepards Drive Processing Plant is well within regulatory limits and effectively controlled.
- The findings demonstrate that current operational controls are working effectively, and there is no significant occupational health risk from dust exposure at this time.
- Continued monitoring and maintenance of existing controls will ensure ongoing compliance and protection of employee health.

Applicable Dust Exposure Limits (EH40)

For **general workplace dust** (applicable to RDF/MDR plants):

Dust Type	WEL (8-hr TWA)
Inhalable dust	10 mg/m ³
Respirable dust	4 mg/m ³

These limits apply where the dust does not have a specific toxic classification.

Monitoring Results – Overview



Workplace dust exposure monitoring

Date	Day	Time from	Time to	Total duration	STEL Threshold	TWA Threshold	Total Dust Exposure	PM4.25		
								Total dust exposure	% of TWA	STEL Alerts
19/02/2026	Thu									
18/02/2026	Wed	09:13	16:23	07:09	1	1		0.082	8	0
17/02/2026	Tue	16:36	11:57	19:21	1	1		0.01	0.96	0
13/02/2026	Fri	08:35	16:20	07:45	1	1		0.02	2	0
17/12/2025	Wed	15:49	01:44	09:55	1	1		0.006	0.61	0
16/12/2025	Tue	08:17	15:44	07:27	1	1		0.008	0.84	0
05/12/2025	Fri	07:50	16:04	07:37	1	1		0.033	3	0
04/12/2025	Thu	14:43	15:32	0:48	1	1		0.052	5	0
03/12/2025	Wed	08:12	15:32	07:13	1	1		0.066	7	0
27/11/2025	Thu	08:23	13:05	04:49	1	1		0.011	1	0
19/11/2025	Wed	12:53	16:12	03:19	1	1		0.012	1	0
18/11/2025	Tue	08:07	16:12	08:03	1	1		0.025	3	0
17/11/2025	Mon	07:50	16:04	07:37	1	1		0.01	1	0
09/04/2025	Wed	08:07	16:12	08:03	1	1		0.006	0.62	0
08/04/2025	Tue	08:00	16:15	08:15	1	1		0.106	11	0
01/04/2025	Tue	07:53	16:54	07:59	1	1		0.094	9	0
12/03/2025	Wed	08:15	16:34	08:29	1	1		0.002	0.21	0

Dust monitor measures PM2.5 / PM10 / PM1.0 with conversion to total dust exposure and % of TWA.

Highest Recorded Results

Location	Total Dust (mg/m ³)	% of TWA
RDF Baler	0.082	8%
Cardboard line	0.066	7%
Cardboard line	0.052	5%
Paper line	0.033	3%
MDR Pre-pick line	0.025	3%

All other readings are <2% of WEL.

Compliance Assessment

Comparison to WEL

Parameter	Highest Recorded	WEL	Compliance
Total dust exposure	0.082 mg/m ³	10 mg/m ³	WELL BELOW LIMIT
% of TWA	8%	100%	WELL BELOW LIMIT

Conclusion

Exposure is approximately:

- ✓ 92% below the workplace exposure limit
- ✓ This indicates very low occupational dust exposure.

PM Monitoring Results

Typical values recorded:

Particle Size	Typical Range
PM2.5	0.006 – 0.078 mg/m ³
PM10	0.009 – 0.119 mg/m ³
PM1.0	0.005 – 0.067 mg/m ³

These levels are consistent with well-controlled waste processing environments.

Higher readings occur in expected areas (dust generation points):

- RDF baler
- Cardboard line
- Pre-pick line

Short-Term Exposure (STEL)

- ✓ Reading shows **0 STEL alters**.

This demonstrates that ReGen have:

- No short-term peaks detected.
- No rapid high dust events.
- A stable operating condition.

Risk Assessment Summary per location

Dust Exposure Risk Level

Area	Risk Rating	Justification
RDF Baler	Low	Highest reading but <10% WEL
Cardboard line	Low	Expected fibre dust
Paper line	Low	Paper fibre particulate
Pre-pick line	Low	Manual sorting activity
MDR computer operator	Very Low	Control room environment

Overall risk:

LOW

Control measure on site:

- ✓ Regular cleaning and maintenance of plant
- ✓ Dust masks available to all staff
- ✓ Face fitting kits on site
- ✓ Dust awareness training
- ✓ Ventilation around site

Date	Day	Time from	Time to	Total duration	STEL Threshold	TWA Threshold	Total Dust Exposure	PM 4.25		
								Total dust exposure	% of TWA	STEL Alerts
19/02/2026	Thu									
18/02/2026	Wed	09:13	16:23	07:09	1	1	1	0.082	8	0
17/02/2026	Tue	16:36	11:57	19:21	1	1	1	0.01	0.96	0
13/02/2026	Fri	08:35	16:20	07:45	1	1	1	0.02	2	0
17/12/2025	Wed	15:49	01:44	09:55	1	1	1	0.006	0.61	0
16/12/2025	Tue	08:17	15:44	07:27	1	1	1	0.008	0.84	0
05/12/2025	Fri	07:50	16:04	07:37	1	1	1	0.033	3	0
04/12/2025	Thu	14:43	15:32	0.48	1	1	1	0.052	5	0
03/12/2025	Wed	08:12	15:32	07:13	1	1	1	0.066	7	0
27/11/2025	Thu	08:23	13:05	04:49	1	1	1	0.011	1	0
19/11/2025	Wed	12:53	16:12	03:19	1	1	1	0.012	1	0
18/11/2025	Tue	08:07	16:12	08:03	1	1	1	0.025	3	0
17/11/2025	Mon	07:50	16:04	07:37	1	1	1	0.01	1	0
09/04/2025	Wed	08:07	16:12	08:03	1	1	1	0.006	0.62	0
08/04/2025	Tue	08:00	16:15	08:15	1	1	1	0.106	11	0
01/04/2025	Tue	07:53	16:54	07:59	1	1	1	0.094	9	0
12/03/2025	Wed	08:15	16:34	08:29	1	1	1	0.002	0.21	0